

K Redline

KR200S

High tech ultra-light powered 4000 Watt system

Features:

- K** Unique performance-to-size ratio
- K** High power 127dB continuous, 133dB peak
- K** Fitted with integral handles and castors
- K** Line array emission wavefront
- K** Integrated mounting system
- K** DSP on board with 16 dedicated presets
- K** Remote PC control software (RS485)
- K** Ultra fast set-up and dismantling system

Applications:

- K** Theatrical sound reinforcement
- K** Concert halls, clubs, houses of worship
- K** Portable and installed audio-visual systems
- K** Cinema and special effects



The **KR200S** is a high performance ultra-slim powered two way system designed for use with small to medium wavefront systems, in both mobile and install applications. The **KR200S** includes.

The **KL18ma** features a 1600 watt 18" drive unit with magnet structure and suspension engineered for maximum linear excursion.

The ultra-light reflex cabinet is fitted with two pocket handles and one 35mm pole mounting point for easy installation with every satellite speaker on it. It features large area porting to reduce air noise.

The **KR200S** ultra-slim satellite features a line array of 2" high efficiency drive units with neodymium magnet structure and suspensions engineered for maximum linear excursion and minimum noise problems. The ultra-strong chassis ensures high resistance and durability also with hardest work conditions.

All the **KR200S** components are designed by **K-array** R&D department and custom made under **K-array** control quality system.

Technical Details (one side system)

Acoustics	
Power handling	800(sub) + 500(sat) w ¹
Max power	1200(sub) + 1200(sat) w ²
Impedance	8Ω(sub) + 8Ω(sat)
Operating frequency range	30Hz - 19 KHz +/- 3dB (preset relating) ³
Frequency range	35Hz - 19 KHz +/- 3dB (preset relating) ⁴
SPL 1W/1mt	97 dB(sub) 101 dB(sat) ⁷
Maximum SPL	127dB continuous - 133 dB peak ⁶
Cross over	
Type	DSP controlled preset relating
Frequency	150 Hz minimum (preset relating) ⁷
Transducers	
Low frequency	1 x 18" Neodymium speakers with 3" voice coil
High frequency	32 x 2" Neodymium speakers with 0,75" voice coil
Audio Input	
Connectors	male + female parallel 3 poles balanced XLR
Wiring	Pin1 = ground / Pin2 = hot / Pin3 = cold
Audio powered Output	
Connector	Female Speakon
Wiring	Pin1+ = CH1+ / Pin1- = CH1- / Pin2+ = N.C. / Pin2- = N.C.
Remote control Input	
Connectors	1 x female 8 poles RJ45
Power Input	
Connectors	2 x PowerCon IN/OUT
Amplifiers	
Type	1 modules class D - DSP controlled
Subwoofer power	1000 Watt ⁸
Satellite power output	1000 Watt ⁸
Protections	Dynamic limiter, over current, over temp, short circuits
AC power	
Operating range	Standard 210 - 240 Vac 50Hz (standard) Optional 100 - 120 Vac 60Hz (optional)
Max continuous and burst current	Standard 6A(>10 sec) - 12A (<1 sec) Optional 10A(>10 sec) - 20A (<1sec)
Physical	
Measures	46.5 x 46.5 x 58.5 cm (KL18ma) 5.5 x 7 x 200 cm (KR200)
Weight	20 Kg (KL18ma) 9 Kg (KR200)

New materials and design are introduced into existing products without previous notice.
Present systems may differ in some respects from those presented in this brochure.

HP Sound Equipment s.r.l. - www.k-array.com

Viale Roma 7/i 50037 San Piero a Sieve (Firenze) Italy - tel +39 055 8487222 fax +39 055 8487238 e-mail: info@k-array.com